

**Implements
Designed
for Your
Lifestyle.**



ATV Attachments

**A line of multi-purpose ATV attachments
that are built to last.**





ATV — Attachments that are rugged, reliable, and ready to go when you are.

FOD-15 Flip-Over Disc

Till. Flip. Transport. Till. Flip...

- Patented design allows disc to easily be changed from transport to working position.
- Eight 16" notched blades for positive trash cutting and soil penetration.
- Disc gangs are at 20° angle for optimum cutting.
- Ideal for wildlife food plots.



Ideal for wildlife food plots

FOD-15 Flip-Over Disc Specifications

HP Requirements (minimum).....	18 HP or 350 cc
Construction.....	Welded steel
Operating width (ft/mm).....	5/1.5
Overall width of frame (in/mm)	53/1325
Overall height (in/mm).....	35/875
Length with tongue (in/mm).....	70/1750
Tire size	4" x 12" pneumatic
Axles	1" square
Bearings	Cast iron w/grease zerks
Shipping weight (lb./kg).....	240/109
Product computer number	940280
Optional weight (6 plates and bolts)	
Shipping weight (lb./kg).....	190/86
Product computer number	940295

Flip-Over Harrow

Harrow. Flip. Transport. Flip. Harrow. Flip...

- Harrow easily changes from transport to working position.
- Staggered tooth pattern for maximum field coverage.
- Adjustable spike tooth angle allows the harrow to work as a smoothing tool or aggressive tillage tool.
- Excellent tool for riding arenas.



Excellent tool for riding arenas

Flip-Over Harrow Specifications

HP Requirements (minimum).....	18 HP or 350 cc
Construction.....	Welded steel
Operating width (ft/mm).....	5/1.5
Overall width of frame (in/mm)	62/1575
Length with tongue transport (in/mm)	83/2413
Length with tongue working position (in/mm)...	95/2413
Tire size	4" x 12" pneumatic
Hitch type	Clevis type
Number of tooth bars.....	5
Number of spike teeth.....	42
Tooth pattern.....	Staggered
Spike material.....	Forged high-carbon steel
Tongue weight in transport (lb./kg)	58/26
Shipping weight (lb./kg).....	205/93
Product computer number	940500

Decades of experience and innovation have set us apart and captured the choice of ATV enthusiasts.

ATV — Landscape Rakes

- Nothing handles clean up and grooming jobs better than our ATV landscape rakes.
- Spring steel tines are spaced at 1" intervals for exceptional performance in pick-up, grooming, and material distribution.
- Chassis utilizes a clevis-type hitch for easy hook up.



Landscape Rake Specifications

Type	Pull type
Width (ft/mm)	4/1.2
Width (ft/mm)	5/1.5
Width (ft/mm)	6/1.8
Hitch type	Clevis type
Angle positions.....	5
Tines	5/16 x 1 heat treated
Height adjustment.....	Turnbuckle
Raise/lower	Rope pull-lever
Tire/gauge wheels.....	Pneumatic
Shipping weight 4 ft. (lb./kg)	195/188
Shipping weight 5 ft. (lb./kg)	205/93
Shipping weight 6 ft. (lb./kg)	225/102
Product computer number 4 ft.....	341940
Product computer number 5 ft.....	341945
Product computer number 6 ft.....	341950

ATV — Box Scraper

- ATV box scraper offers exceptional utility for all your leveling and grading applications.
- Pneumatic tires are used for transport and gauge wheels.
- Great for moving dirt, grading and spreading topsoil, gravel or driveway rocks.



Box Scraper Specifications

Type	Pull type
Width (in/cm)	42/1066
Hitch type	Clevis
Height adjustment.....	Turnbuckle
Raise/lower	Rope pull-lever
Tire/gauge wheels.....	Pneumatic
Shipping weight 4 ft. (lb./kg)	190/86
Product computer number	341960

Flexible design allows the chassis to accommodate either the landscape rake tine bar assembly or the box scraper assembly. Offering the operator enhanced versatility with this tool.



Models:
 ATVK-350
 ATVK-370
 ATVK-390

ATV — Electric Seeder/Spreaders

- Maintenance-free 1-bushel polyethylene hopper is translucent – providing a material sight gauge.
- A 12-volt electric motor with variable speed control for exceptional spread coverage for most seeding conditions.
- Complete wiring package included.
- Perfect for seeding pastures and covering crops, spreading granular fertilizer and other granular materials.
- Control lever is positioned to allow the operator to easily reach it.

Pull-type Seeder/Spreaders — Ground Driven

- Model PS-5 (#420940) ground driven for easy operation.
- Wheel drive can be disconnected for transport.
- Cone shaped steel hopper provides easy material flow, features a five bushel capacity.
- 15 x 6.00-6 (4-ply) tires with tread width of 39.5" is standard.
- Accurate broadcasting of grass seed, wheat and fertilizer.



Flip-Over Culti-Packer

HP Requirement (minimum) 18 HP or 350 cc
 Construction Welded steel
 Operating width 50"
 Tire size 4" x 12" pneumatic
 Culti-packer wheels (22) Cast iron
 Shipping weight 274 lbs.
 Product computer number 940400

**Implements
 Designed
 for Your
 Lifestyle.**

WORKSAVER, INC. has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. WORKSAVER, INC. is not responsible for differences between specifications or illustrations contained in this publication and the actual equipment.



WorkSaver, Inc.

P.O. Box 100, Litchfield, IL 62056-0100
 Phone: 217-324-5973 • Fax: 217-324-3356
 E-mail: sales@worksaver.com
 Web: www.worksaver.com

Distributed by: