

RB 10 SERIES

Up to 24 HP • 48", 60"



FEATURES:

- Cat. 1 hitch
- Roll-formed moldboard for excellent loading & unloading of soil
- High carbon 1/2" x 6" single bevel cutting edge
- 3 forward and reverse angle settings
- Powder coat tractor matching colors
- Optional Equipment: Parking Stand

MODELS	WIDTH	MOLDBOARD HEIGHT	CUTTING EDGE	HITCH	MAX TRACTOR HP	WEIGHT
RB10-48	48"	12"	1/2" x 6" Reversible	Cat. 1	24	166
RB10-60	60"	12"	1/2" x 6" Reversible	Cat. 1	24	176

RB 15 SERIES

Up to 25 HP • 48", 60"



FEATURES:

- Cat. 1 hitch
- Roll-formed moldboard for excellent loading & unloading of soil
- High carbon 3/8" x 3" single bevel weld on cutting edge
- 5 forward and reverse angle settings
- Powder coat tractor matching colors
- Optional Equipment: Parking Stand

**QUICK HITCH
COMPATIBLE**

MODELS	WIDTH	MOLDBOARD HEIGHT	CUTTING EDGE	HITCH	MAX TRACTOR HP	WEIGHT
RB15-48	48"	15" x 3/16"	3/8" x 3" Welded	Cat. 1	25	164
RB15-60	60"	15" x 3/16"	3/8" x 3" Welded	Cat. 1	25	180

RB 20 SERIES

Up to 40 HP • 60", 72", 84"



FEATURES:

- Cat. 1 hitch
- Roll-formed moldboard for excellent loading and unloading of soil
- Heavy 5" channel moldboard support
- 1/2" x 6" reversible cutting edges
- 5 forward and reverse angle settings
- Powder coat tractor matching colors
- Optional Equipment: Parking Stand

**QUICK HITCH
COMPATIBLE**

MODELS	WIDTH	MOLDBOARD HEIGHT	CUTTING EDGE	HITCH	MAX TRACTOR HP	WEIGHT
RB20-60	60"	15" x 3/16"	1/2" x 6" Reversible	Cat. 1	40	223
RB20-72	72"	15" x 3/16"	1/2" x 6" Reversible	Cat. 1	40	250
RB20-84	84"	15" x 3/16"	1/2" x 6" Reversible	Cat. 1	40	290

Specifications subject to change without notice

RB22 SERIES

Up to 40 HP • 60", 72", 84"



FEATURES:

- Cat. 1 hitch
- 1/2" x 6" reversible cutting edges
- Tilt, angle and manual pin offset setting
- Roll-formed moldboard for excellent loading and unloading of soil
- 5 forward and 5 reverse angle setting
- Powder coat tractor matching colors
- Optional Equipment: Parking Stand

**QUICK HITCH
COMPATIBLE**

MODELS	WIDTH	MOLDBOARD HEIGHT	CUTTING EDGE	HITCH	MAX TRACTOR HP	WEIGHT
RB22-60	60"	15" x 3/16"	1/2" x 6" Reversible	Cat. 1	40	277
RB22-72	72"	15" x 3/16"	1/2" x 6" Reversible	Cat. 1	40	304
RB22-84	84"	15" x 3/16"	1/2" x 6" Reversible	Cat. 1	40	355

RB40 SERIES

Up to 75 HP • 72", 84", 96"



FEATURES:

- Cat. 1 hitch
- 1/2" x 6" reversible cutting edge
- Tilt, angle and ratchet adjust offset
- Roll-formed moldboard for excellent loading and unloading of soil
- 5 forward and 5 reverse angle setting
- Powder coat tractor matching colors
- Optional Equipment: Parking Stand

**QUICK HITCH
COMPATIBLE**

MODELS	WIDTH	MOLDBOARD HEIGHT	CUTTING EDGE	HITCH	MAX TRACTOR HP	WEIGHT
RB40-72	72"	16" x 1/4"	1/2" x 6" Reversible	Cat. 1 & 2	75	503
RB40-84	84"	16" x 1/4"	1/2" x 6" Reversible	Cat. 1 & 2	75	541
RB40-96	96"	16" x 1/4"	1/2" x 6" Reversible	Cat. 1 & 2	75	578

Specifications subject to change without notice

BB10 SERIES

Up to 24 HP • 48", 60"



FEATURES:

**QUICK HITCH
COMPATIBLE**

- Cat. 1 hitch
- Roll-formed moldboard for excellent loading and unloading of soil
- 3/16" End Plates
- 1/2" x 6" reversible cutting edges
- 1/4" wall x 3-1/2" tubing main frame
- Reversible lift pins
- Powder coat tractor matching colors

MODELS	WIDTH OF CUT	MOLDBOARD HEIGHT	BOX DEPTH	HITCH	SIDE PLATES	NO. SHANKS	WEIGHT
BB10-48	48"	12"	18"	Cat. 1	3/16"	4	248
BB10-60	60"	12"	18"	Cat. 1	3/16"	4	258

BB15 SERIES

Up to 25 HP • 48", 60"



FEATURES:

**QUICK HITCH
COMPATIBLE**

- Cat. 1 hitch
- Roll-formed moldboard for excellent loading and unloading of soil
- 3/16" End Plates
- 1/4" wall x 3-1/2" tubing main frame
- 3/8" x 3" high carbon weld on cutting edges
- Reversible lift pins
- Powder coat tractor matching colors

MODELS	WIDTH OF CUT	MOLDBOARD HEIGHT	HITCH	HITCH PLATES	SIDE PLATES	NO. SHANKS	WEIGHT
BB15-48	48"	15"	Cat.1	3/8"	1/4" x 15" x 21-1/2"	4	309
BB15-60	60"	15"	Cat.1	3/8"	1/4" x 15" x 21-1/2"	5	351

BB20 SERIES

Up to 40 HP • 48" - 84"



FEATURES:

**QUICK HITCH
COMPATIBLE**

- Cat. 1 hitch
- Roll-formed moldboard for excellent loading and unloading of soil
- 3/8" End Plates
- 1/2" x 6" reversible cutting edges
- 1/4" x 4" tubing main frame
- Clevis style hitch
- Powder coat tractor matching colors

MODELS	WIDTH OF CUT	MOLDBOARD HEIGHT	HITCH	HITCH PLATES	SIDE PLATES	NO. SHANKS	WEIGHT
BB20-48	48"	16"	Cat.1	3/8"	3/8" x 17" x 24"	4	397
BB20-54	54"	16"	Cat.1	3/8"	3/8" x 17" x 24"	4	418
BB20-60	60"	16"	Cat.1	3/8"	3/8" x 17" x 24"	5	440
BB20-66	66"	16"	Cat.1	3/8"	3/8" x 17" x 24"	5	467
BB20-72	72"	16"	Cat.1	3/8"	3/8" x 17" x 24"	6	494
BB20-84	84"	16"	Cat.1	3/8"	3/8" x 17" x 24"	7	575

BB30 SERIES

Up to 60 HP • 60" - 96"



FEATURES:

**QUICK HITCH
COMPATIBLE**

- Cat. 1 hitch
- Roll-formed moldboard for excellent loading and unloading of soil
- 3/8" End Plates. 1/2" Hitch Plates
- 1/2" x 6" reversible cutting edges
- 3-Point shank with replaceable tips
- Clevis style pins
- Powder coat tractor matching colors

MODELS	WIDTH OF CUT	MOLDBOARD HEIGHT	HITCH	HITCH PLATES	SIDE PLATES	NO. SHANKS	WEIGHT
BB30-60	60"	16"	Cat.1	1/2"	3/8" x 17" x 24"	5	541
BB30-66	66"	16"	Cat.1	1/2"	3/8" x 17" x 24"	5	573
BB30-72	72"	16"	Cat.1	1/2"	3/8" x 17" x 24"	6	606
BB30-84	84"	16"	Cat.1	1/2"	3/8" x 17" x 24"	7	682
BB30-96	96"	16"	Cat.1	1/2"	3/8" x 17" x 24"	8	752

LR-10 SERIES

Up to 24 HP • 48", 60"



FEATURES:

- Cat. 1 hitch
- High carbon teeth on 1" spacing
- Five forward and reverse angle settings
- Reversible lift pins
- Powder coat tractor matching colors

MODELS	WORKING WIDTH	TINE HEIGHT	HITCH	MAXIMUM TRACTOR HP	WEIGHT
LR10-48	48"	12"	Cat. 1	24	168
LR10-60	60"	12"	Cat. 1	24	178

LR-20 SERIES

Up to 45 HP • 60", 72", 84", 96"



FEATURES:

**QUICK HITCH
COMPATIBLE**

- Cat. 1 hitch
- High carbon teeth on 1" spacing
- Five forward and reverse angle settings
- Formed tine with lockable tine spacing
- 1" spacing between tines
- Reversible lift pins
- Powder coat tractor matching colors
- Optional Equipment: gauge wheels, parking stand

MODELS	WORKING WIDTH	TINE HEIGHT	HITCH	MAXIMUM TRACTOR HP	WEIGHT
LR20-60	48"	15"	Cat. 1	45	195
LR20-72	60"	15"	Cat. 1	45	215
LR20-84	84"	15"	Cat. 1	45	235
LR20-96	96"	15"	Cat. 1	45	255