

"Always one step ahead"[®]

FINISHING MOWERS



Head Office:

Via Gino Tonutti, 3
33047 Remanzacco (Udine) Italy
Phone ++39 0432 667015
Fax ++39 0432 668282

Factories:

Remanzacco (UD) Italy
Rivignano (UD) Italy
Vezzano (RE) Italy

tonutti[®]
SINCE 1864



TONUTTI FM SERIES FINISHING MOWERS


The Professional Solution for lawns, sod farms, estates, school grounds, golf courses and parks. The FM Tonutti Finishing Mowers make large mowing jobs short.

The Tonutti FM Finishing Mower is an extremely well equipped machine that includes as standard features what others offer only as optionals:

- Rear Discharge Baffling
- High quality tempered steel blades
- Unique and very innovative Height Adjustment
- Large Solid Rubber Tires 210 x 80 mm
- Heavy Duty PTO Shaft Double Safety Collar Cat. S4
- Double Central Pulley
- Very High Quality Main Frame (6 mm for models 150/180 and 210)
- Bent reinforcement around the bottom edge
- Wheels with Mud Guards
- Slide adjustment of the gearbox for belt tension
- Easy Access to belts by means of winged screws
- Pivoting upper and lower linkages for better following of the ground contours
- Lower linkage adjustable in length to adapt to different tractor sizes
- PTO shaft with collar

Optional :

- Front Roller 150 x 100 mm (Poly Roller)
- Mulching Kit



TECHNICAL SPECIFICATIONS

MODELS	FM 120	FM 150	FM180	FM210
CUTTING WIDTH	1200 mm (48")	1500 mm (60")	1800 mm (72")	2100 mm (82")
CUTTING HEIGHT	30 mm (1,18") - 75 mm (2,95")			
TRACTOR POWER HP	15-30	20-40	30-50	40-60
3-P. CAT. HITCH	I	II	II	II
PTO SHAFT	Heavy Duty S 4 with Double Safety Collar			
TIRES	Solid Rubber Tires with ball bearings 210 x 80 mm			
NO. OF BLADES	3	3	3	3
BLADE MATERIAL	Tempered Steel			
BLADE SIZES	422x50x6	513x50x6	623x60x6	725x60x6
LENGTH X WIDTH X THICKNESS (MM)				
BLADE SPEED RPM	3.126	2.645	2.234	2.025
PTO SPEED RPM	540	540	540	540
WEIGHT	168 kg	199 kg	228 kg	385 kg
OIL TYPE	EP SAE 80W - 90			
OIL AMOUNT	0,90 l. (Gall. 0,20)			

TONUTTI reserves the right to make changes or add improvements at any time without notice. The information contained herein is general in nature and is not intended for specific application purposes.

Tonutti U.S.A.:
S&T Distributing, Inc.
1909 Thomas Road
Memphis TN 38134
Phone (901) 385 8841
Fax (901) 385 8288
e-mail: stmf@bellsouth.net
www.tonuttiusa.com

Tonutti Russia:
G.M.T. Limited
3 Tekhnicheskaya Street
Perm 614070 RUSSIA
Phone 007 (3422) 909 096
Fax 007 (3422) 909 096
e-mail: gmlltd@mail.perm.ru
www.tonuttirusssia.com

