

## 200 Series Air-Cooled MidMount™



A great first step toward the fleet of your dreams.

### Model 220

- 20 hp, 2-cylinder Kohler Command engine
- Fully padded, high-back, vinyl-covered ComfortZone™ seat
- 48-inch DuraMax® deck



The turf care professional's perfect introduction to Grasshopper True ZeroTurn™ performance. The reliable, economical 200 Series mowers deliver a quality cut and powerful, air-cooled performance in a compact package ideal for tight-quarters mowing. Enjoy the maneuverability of a walk-behind without the fatigue, so operators can mow longer and deliver quality results every time.

- Forward mowing speeds up to 10 mph – or up to 6.55 acres per hour – make quick work of high-capacity, straightaway mowing applications.
- Durable, design-matched hydrostatic transmissions provide smoother response and less maintenance.
- Only five Access-Eze™ lubrication points cut maintenance time up to 80%.
- A compact wheelbase provides easy transport on trailers and fits easily into shops or garages with limited space.
- Each DuraMax® deck easily converts from side discharge to optional mulching to vacuum collection.
- Special-order rear-discharge decks provide the quality cut you expect from Grasshopper.



### Standard Features for 200 Series

- Rugged, air-cooled, OHV engines with horizontal crankshaft and pressure lube for smooth, reliable operation
- Design-matched G<sup>2</sup> transmissions with 7 micron absolute filters
- CoolFan™ hydro cooling system for Models 223 and 227
- DuraMax® decks with anvil-edged design for exceptional durability
- Deep-cushioned ComfortZone™ seat with coil-spring suspension
- Hydra-Smooth™ dual swing-out adjustable levers
- Heavy-duty, remote-mounted air filter with replaceable element
- ROPS with adjustable seat belt
- Disc brakes
- Hour meter

### Model 223

- 23 hp, 2-cylinder Kohler Command Pro engine
- CoolTemp Cordura® ComfortZone™ seat with lumbar support
- CoolFan™ hydro cooling system
- 52- or 61-inch DuraMax® deck



### Options for 200 Series

- Quik-D-Tatch® PowerVac™ Collection Systems
- Down Discharge™ mulching packages
- Dedicated 4X Rear Discharge™ deck for selected models
- TrimMaster™ heavy-duty, anti-scalp roller for 52-, 61- and 72-inch models
- Electric Height Adjustment
- DuraGuard™ bumper
- DuraFlex™ suspension forks
- Halogen work lights
- Extended levers for taller operators
- ComfortReach™ “no tools” lever adjustment
- Big Boy wide-seat conversion kit
- Premier suspension seat
- Adjustable cup holder
- Foldable ROPS with adjustable seat belt
- Bar tread, low-pressure tires for 61- and 72-inch models
- Edge-EZE™ edger
- Shielded Sprayer
- Sunshade Canopy (for ROPS)
- Yellow beacon light
- Filter minder

### Model 227

- 27 hp, 2-cylinder Kohler Command Pro engine
- CoolTemp Cordura® ComfortZone™ seat with lumbar support
- CoolFan™ hydro cooling system
- 52-, 61- or 72-inch DuraMax® deck



Be more productive with the addition of a PowerVac™ Collection System or other implements. Ask for specifications or visit [grasshoppermower.com/implements](http://grasshoppermower.com/implements). Models may be shown with optional equipment.

# Air-Cooled 200 Series MidMount™ Specifications

MODEL-CUTTING WIDTH	220-48	223-52 & 223-61	227-52 & 227-61 & 227-72
<b>ENGINE</b>			
Type/Horsepower/Cylinders	Kohler Command/20 hp/V-Twin	Kohler Command Pro/23 hp/V-Twin	Kohler Command Pro/27 hp/V-Twin
Displacement	38.1 cu. in. (624 cc)	41.1 cu. in. (674 cc)	44.2 cu. in. (725 cc)
Crankshaft/Lubrication System	Horizontal/Pressure Lube/Filter	Horizontal/Pressure Lube/Filter	Horizontal/Pressure Lube/Filter
Fuel	Gasoline - unleaded		
Fuel Capacity	12 U.S. Gal. (38 l)		
Air Cleaner	Heavy-duty, cyclonic, remote mounted dual air cleaner with replaceable element.		
Muffler	Ultra quiet, single, industrial type.		
<b>DURAMAX® DECKS</b>			
Construction (Robotic-welded steel)	Double-layered, 10-gauge plus 7-gauge formed-steel laminate spindle plane – 30% thicker than 1/4 in. (7.97 mm) – with 7-gauge skirts for geometric strength. 1/2-in. (12.7 mm) reinforcement on front edge of deck.		
Blades (Tempered, alloy steel)	-48 (2) 18 in. (45.7 cm) (1) 15 in. (38.1 cm)	-52 (3) 18 in. (45.7 cm) -61 (3) 21 in. (53.3 cm)	-52 (3) 18 in. (45.7 cm) -61 (3) 21 in. (53.3 cm) -72 (3) 25 in. (63.5 cm)
Spindle Assemblies	Spindle head designed to eliminate fiber wrap. 2.5 cm (approx 1 in.) O.D. shaft. Double bearings, greasable from top of deck. Spindle cones on 52-, 61- and 72-inch decks shield housing and lower bearings from fiber wrap and dirt ingestion.		
Spindle Housing	Machined aluminum housing on 48- to 61-inch decks. Cast iron on 72-inch deck.		
Blade Drive	Belt drive with single Kevlar V-belt and idler arm tensioning.		
<b>STARTER &amp; ELECTRICAL SYSTEM</b>			
Maintenance-Free Battery/Starter	12 Volt/solenoid shift		
Ignition	Breakerless		
Interlock System	Prevents engine start when PTO clutch is engaged or steering levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.		
<b>ULTIMATE OPERATOR STATION™</b>			
Seat	Iso-mounted, high-back, deep-cushioned, foam-padded, vinyl-covered, padded arms/backrest with coil spring suspension.	Iso-mounted, high-back, deep-cushioned, foam-padded, Cordura-covered, padded arms/backrest with lumbar support and coil-spring suspension. Optional Premier suspension seat.	
Suspension	InFrame™ suspension		
Console-Mounted Instruments	Hour meter, parking brake indicator light, ignition switch, choke and push/pull PTO switch.		
Work Lights	Optional		
Hour Meter	Standard		
<b>TRANSMISSION &amp; STEERING</b>			
Type	Design-matched G <sup>2</sup> hydrostatic system, HydroGear variable displacement piston-type pumps and Parker/Ross wheel motors.	Design-matched G <sup>2</sup> hydrostatic system with auxiliary cooling fans, HydroGear variable displacement piston-type pumps and high-torque Parker wheel motors.	
Transmission Fluid	Grasshopper Hydro-Max™ synthetic fluid withstands high and low temperature extremes for extended change intervals.		
Filtration	7 micron absolute, spin-on		
Speed	0 – 8.5 mph (0 – 13.7 kph) forward 0 – 6.0 mph (0 – 9.7 kph) reverse	0 – 9.5 mph (0 – 15.3 kph) forward 0 – 6.0 mph (0 – 9.7 kph) reverse	0 – 10.0 mph (0 – 16.1 kph) forward 0 – 6.0 mph (0 – 9.7 kph) reverse
Turning Radius	True zero degree, turns within own length with counter-rotating, independently powered drive wheels.		
Steering	One- or two-handed operation with adjustable Hydra-Smooth™ dual levers that automatically return to neutral from either forward or reverse position.		
Brakes	Dynamic braking through hydrostatic transmission/disc parking brakes, one for each drive wheel.		
<b>TIRE SIZES</b>			
Drive Wheels – Std	-48" & -52" Models	23x9.50x12 turf	23x10.50x12 turf
Drive Wheels – Std	-61" & -72" Models	N/A	24x12.00x12 turf
Drive Wheels – Opt	-61" & -72" Models	N/A	24x12.00x12 bar tread
Front Casters – All Models		13x5.00x6 rib tread, tubeless	13x6.50x6 rib tread, tubeless
<b>DIMENSIONS</b>			
Mulch Width*/Length	-48" Model† -52" Models† -61" Models† -72" Model†	49.5 in.* (125.7 cm)/75.0 in. (190.5 cm) N/A N/A N/A	N/A 53.5 in.* (135.8 cm)/75.0 in. (190.5 cm) 62.5 in.* (158.8 cm)/76.5 in. (194.3 cm) N/A
Height (Seat back/Seat cushion)		46.5 in. (118.1 cm)/31.0 in. (78.7 cm)	47.0 in. (119.4 cm)/31.5 in. (80.0 cm)
Height (ROPS)		69.0 in. (175.3 cm)	69.5 in. (176.5 cm)
<b>WEIGHT</b>			
Uncrated	-48" Model -52" Models -61" Models -72" Model	1030 lbs. (467.2 kg) N/A N/A N/A	N/A 1070 lbs. (485.4 kg) 1120 lbs. (508.0 kg) 1210 lbs. (548.9 kg)

\* Add 1.5 in. (3.8 cm) to width for side discharge with deflector raised.

† DuraMax® Deck mulching package kit weights/order numbers: 48-in. – 25 lbs. (11.3 kg)/504566; 52-in. – 29 lbs. (13.2 kg)/504567; 61-in. – 36 lbs. (16.3 kg)/504569; 72-in. – 44 lbs. (20.0 kg)/504571

All specifications and information contained herein are subject to change without notice. Access-Eze, ComfortReach, ComfortZone, CoolFan, Down Discharge, DuraFlex, DuraGuard, Edge-EZE, Hydra-Smooth, Hydro-Max, MidMount, PowerVac, 4X Rear Discharge, TrimMaster True ZeroTurn, Ultimate Operator Station and View-Eze are trademarks and Grasshopper, the Grasshopper logo, DuraMax, Quik-D-Tatch and Your Next Mower are registered trademarks of the Grasshopper Company. All other products are trademarks or registered trademarks of their respective holders.



**YOUR NEXT MOWER®**

**grasshoppermower.com**

The Grasshopper Company • One Grasshopper Trail  
P.O. Box 637 • Moundridge, KS 67107 U.S.A.  
Telephone: 620-345-8621 • FAX: 620-345-2301

