

Edge-EZE™ Edger

For Grasshopper True ZeroTurn™ Mowers



Optional bracket mounts edger to left side of side-discharge deck and to either side of rear-discharge deck.



Case Study

A two-mile stretch of sidewalk at a golf course equals four miles of edging. It takes two workers with hand-held edgers 16 hours each (or 32 man-hours) of labor to maintain this each time. The same job takes one operator with a Grasshopper and Edge-EZE™ only four hours.

Annual cost of NOT using Grasshopper = \$10,228 Learn more at grasshoppermower.com/edge.

Streamline the edging process and reduce edging time up to 88%!

Edge-EZE™ **delivers a clean, sharp edge** along sidewalks, roadways and driveways, and saves valuable time and labor edging large areas and long runs.

- Replaces two-cycle edgers and multiple operators for increased productivity and huge cost savings.
- Dependable, heavy-duty construction makes Edge-EZE™ ideal for commercial use.
- Depth of cut is 2-1/2 inches (from hub to edge of disc) and creates a clean, sharp edge that will satisfy the most demanding customers.
- Edge-EZE™ maintains established edge at up to 500 ft./min.
- Manual edger is perfect for maintaining established edges. Lever raises blade for easy transport.
- Optional electric actuator provides additional down pressure for edging in overgrown or tough conditions. Actuator also raises blade 4 inches at the touch of a switch to cross sidewalks.
- Edge-EZE™ connects to discharge side of deck in place of standard discharge shield and is held in place with same thumb screw.

Cutting Edge • Edge-Cutting



A reversible, concave, self-sharpening blade and hub assembly maintains a clean, sharp edge from sidewalk, curb or turf.



Edge-EZE™ discharge shield allows you to blow debris off sidewalk into turf.



12-inch vertical adjustment lets you edge from street or ground level, depending on your needs.



Reverse disc by removing one bolt to edge from the turf.

Edge-EZE™ Specifications

FOR DURAMAX® DECKS	48 in. (121.9 cm)	52 in. (132.1 cm)	61 in. (154.9 cm)	72 in. (182.9 cm)
Total width (in down position)	59.25 in. (150.5 cm)	63.25 in. (160.7 cm)	72.25 in. (183.5 cm)	83.25 in. (211.5 cm)
Total width (in up position)	60.25 in. (153 cm)	64.25 in. (163.2 cm)	73.25 in. (186 cm)	84.25 in. (214 cm)
Maximum ground clearance	12.5 in. (31.8 cm)			
Disc diameter/cutting depth	11.0 in. (27.9 cm) / 2.5 in. (6.4 cm)			
Weight (electric)	82 lbs. (37.2 kg)			
Weight (manual)	76 lbs. (34.5 kg)			
Compatibility	200, 300, 400, 600, 700 amd 900 Series Models			

We can edge from either side of the road and still face oncoming traffic to increase visibility and safety.

~ Scott Brewer,
RCI
Slidell, LA

Locate your nearest dealer at grasshoppermower.com.

Models may be shown with optional equipment.

All specifications and information contained herein are subject to change without notice. 4X Rear Discharge, Edge-EZE and True ZeroTurn are trademarks and DuraMax, Grasshopper, the Grasshopper logo and Your Next Mower are registered trademarks of the Grasshopper Company. All other products are trademarks or registered trademarks of their respective holders.

Litho in U.S.A. Form 0310-170889
© 2010 The Grasshopper Company



YOUR NEXT MOWER®

grasshoppermower.com

The Grasshopper Company • One Grasshopper Trail
P.O. Box 637 • Moundridge, KS 67107 U.S.A.
Telephone: 620-345-8621 • FAX: 620-345-2301



Paper contains 10% post-consumer content. 100% recyclable. Check for recycling programs in your area.