

CIMARRON

FORK ATTACHMENTS

CLAMP-ON BUCKET FORKS • TRASH FORKS
QUICK-ATTACH BUCKET FORKS
PALLET FORKS • 3-POINT FORKS



Edney Distributing Co., Inc. • 8485 215th West; Airlake Ind. Park, Lakeville, MN 55044
Phone: (952) 469-5267 • Fax (952) 469-5269 • Email: edneyco@frontiernet.net

www.edneyco.com

CLAMP-ON BUCKET FORKS

BF SERIES CLAMP-ON BUCKET FORKS

Mount easily in seconds to most loader buckets without using tools. Available in 1000, 2000, 3000, 4000 and 6000 lb. capacities. Slidable handle allows forks to be mounted in most positions on the bucket, such as next to the side or back of the bucket. Forks are equipped with handles for ease in mounting and handling. Models ending in "W" are designed for compact loader buckets with bolt-on cutting edges.



SPECIFICATIONS

MODELS	BF-1000	BF-1000W	BF-2000	BF-2000W	BF-3000	BF-4000	BF-6000
LIFT CAPACITY	1000 lbs.	1000 lbs.	2000 lbs.	2000 lbs.	3000 lbs.	4000 lbs.	6000 lbs.
USEABLE TINE LENGTH	32"	32"	36"	36"	42"	42"	49"
MAX. BUCKET LIP THICKNESS	3/4"	1-9/16"	3/4"	1-9/16"	1-1/4"	1-3/4"	2-1/4"
TINE SIZE	2" x 3"	2" x 3"	2" x 3"	2" x 3"	2" x 4"	2" x 4"	3" x 5"
WEIGHT	90 lbs.	90 lbs.	110 lbs.	110 lbs.	150 lbs.	170 lbs.	275 lbs.

CLAMP-ON TRASH FORKS

TF SERIES CLAMP-ON TRASH FORKS

A handy tool that will make moving tree branches and other debris an easy task. An investment in these new quick on and off Clamp-On Trash Forks will increase your front end loader's versatility. Equipped with two heavy screw-lock clamp brackets with handles. Tines are 2" square, 1/4" wall tubing by 20" length. Clamps fit deep into the bucket for added strength.



SPECIFICATIONS

MODELS	TF48	TF54	TF60	TF60W	TF66	TF72	TF72W
BUCKET SIZE	48"	54"	60"	60"	66"	72"	72"
WIDTH	46"	52"	58"	58"	64"	70"	70"
TINES	5	5	6	6	6	7	7
MAX. BUCKET LIP THICKNESS	3/4"	3/4"	3/4"	1-9/16"	3/4"	3/4"	1-9/16"
APPROX. SPACING BETWEEN TINES	8-1/2"	10"	8-1/2"	8-1/2"	10"	9"	9"
WEIGHT	160 lbs.	170 lbs.	180 lbs.	180 lbs.	195 lbs.	210 lbs.	210 lbs.

Specifications subject to change without notice

PALLET FORKS

3750 lb. CAPACITY PALLET FORKS

Fits many popular utility and Skid Steer loaders. ULF Series fits many loaders that measure between 32" ID and 48" OD equipped with 1" or 1-1/8" pins. JLF Series fits John Deere compact and utility loaders equipped with quick-change attachment carrier. The GLF Series fits many utility loaders with euro style quick couplers. The KLF Series fits Kubota loaders equipped with quick couplers. The SSF Series fits Skid Steers and Tractors with universal Skid Steer mount. Equipped with walk through load guard. The fork tines are constructed of Boron Steel and heat treated. All models are equipped with adjustable forks. Fork tines available in 42" and 48" usable lengths. Custom models are available on special order.



SPECIFICATIONS

MODELS	ULF SERIES	JLF SERIES	GLF SERIES	KLF SERIES	SSF SERIES
LIFT CAPACITY	3750 lbs.	3750 lbs.	3750 lbs.	3750 lbs.	3750 lbs.
FORK LENGTH	42", 48"	42", 48"	42", 48"	42", 48"	42", 48"
TINE SIZE	1-3/8" x 4" Solid	1-3/8" x 4" Solid	1-3/8" x 4" Solid	1-3/8" x 4" Solid	1-3/8" x 4" Solid
ADJ. FOR FEATURES	Standard	Standard	Standard	Standard	Standard
LOADER MOUNTS	Fits many loaders frames between 32" ID and 48" OD w/ 1" or 1-1/8" pins	Fits John Deere Loaders w/ Quick-Change Attachment Carrier	Fits Euro Style Quick Coupler Tractor Loaders	Fits Kubota Quick Coupler Tractor Loaders	Universal Skid Steer Mount
FORK STYLE	Rail	Rail	Rail	Rail	Rail
WEIGHT	370 (42"), 385 (48")	380 (42"), 400 (48")	375 (42"), 439 (48")	380 (42"), 400 (48")	375 (42"), 395 (48")

2250 lb. CAPACITY PALLET FORKS

Fits many popular compact loaders. ULF Series fits many loader frames that measure between 28-1/4" ID and 47-1/4" OD equipped with 3/4" or 1" pins. JLF Series fits John Deere compact loaders equipped with quick-change attachment carrier. The SSF and KLF Series fit Compact loaders with Skid Steer style quick couplers. All models are equipped with high visibility load guards and adjustable forks. The rail style fork tines are constructed of high strength steel and heat treated. Fork tines available in 42" usable lengths.



SPECIFICATIONS

MODELS	ULF-2242	JLF-2242	SSF-2242	KLF-2242
LIFT CAPACITY	2250 lbs.	2250 lbs.	2250 lbs.	2250 lbs.
FORK LENGTH	42"	42"	42"	42"
TINE SIZE	1-1/4" x 3" Solid	1-1/4" x 3" Solid	1-1/4" x 3" Solid	1-1/4" x 3" Solid
ADJ. FORK FEATURE	Standard	Standard	Standard	Standard
LOADER MOUNTS	Fits many Compact Loaders that measure between 28-1/4" ID & 47-1/4" OD with 3/4" or 1" pins	Fits John Deere Compact Loaders with Quick-Change Attachment Carrier	Fits Compact Loaders with Skid Steer Style Quick Couplers	Fits Kubota Compact Loaders with Skid Steer Style Quick Couplers
FORK STYLE	Rail	Rail	Rail	Rail
WEIGHT	280	280	280	280

Specifications subject to change without notice

QUICK-ATTACH BUCKET FORKS

1200 UNIVERSAL SERIES

Provide increased production and versatility for Compact Tractor Front End Loaders. Turns your loader into a forklift in seconds. Installation requires welding mounting brackets to the bucket's top lip or spill plate. The forks then mount easily in seconds by simply curling the bucket and driving into the forks - then leveling the bucket, forks automatically lock in place. Safety lock system to hold forks in place; rod made of 4140 high carbon steel and forks have a safety rating of two times the stated capacity.



SPECIFICATIONS

MODEL	MAX LOAD CAPACITY TINE CTR.	FITS BUCKET OPENINGS	TINE HEIGHT	TINE LENGTH	ADJ. WIDTH	WEIGHT	ROD SIZE	TINE SIZE	NO. OF BRACKETS
1200 UNIV	1200 lbs.	25"	31"	36"	60"	185 lbs.	1-1/4" x 5'	1" x 4"	3

3-POINT FORKS

3-POINT SERIES

Are ideal for picking up and moving pallets and bins. Models 1200, 1500 and 2000 are equipped with category 1, 3-pt. hitches and 41" length nonadjustable tines and available in 1200 lb., 1500 lb., and 2000 lb. capacities. Model 1500-A forks are equipped with 41" length adjustable tines and available in 1500 lb. capacities. Model 3500 series forks are equipped with ITA Class II forks and a quick hitch compatible category 1 and 2, 3-point hitch. Fork tines are adjustable from 10" to 36" center to center. 3750 lb. capacity fork tines are available in 42" and 48" lengths.



SPECIFICATIONS

MODELS	1200	1500	2000	1500-A	3542	3548
LIFT CAPACITY	1200 lbs.	1500 lbs.	2000 lbs.	1500 lbs.	3750 lbs.	3750 lbs.
FORK LENGTH	41"	41"	41"	41"	42"	48"
TINE SIZE	2" x 4" x 3/16" Tubing	1" x 4" Solid	1-1/4" x 4" Solid	1-1/4" x 4" Solid	1-3/8" x 4" Solid	1-3/8" x 4" Solid
FORK CENTERS	26"	26"	26"	Adjustable 4" to 26"	Adjustable 10" to 36"	Adjustable 10" to 36"
WEIGHT	90 lbs.	160 lbs.	180 lbs.	300 lbs.	300 lbs.	315 lbs.

Specifications subject to change without notice

CIMARRON

Edney Distributing Co., Inc.
8485 215th West; Airlake Ind. Park, Lakeville, MN 55044
Phone: (952) 469-5267 • Fax (952) 469-5269
Email: edneyco@frontiernet.net • Website: www.edneyco.com