

*Worksaver.*

*Designed.  
Engineered.  
Remarkable  
Value.*



**WORKSAVER®**

# **Compact Tractor Grapple Rake Attachment**

**Designed for compact tractors up to 40 horsepower that are equipped with a front loader. This 60-inch wide grapple allows the acreage owner unsurpassed versatility in clearing brush, piling limbs or orchard maintenance.**



# Worksaver® Compact Tractor Grapple Rake Attachment

- Ideal for loading limbs, orchard prunings, raking and piling brush and other hard to handle materials.
- Unique upper grapple design provides clamping force to hold material securely.
- Design to be used with compact tractors of 40 HP or less.
- Design allows brush and other materials to be picked up while leaving the dirt.
- Great for picking up / piling cut limbs and treetops when clearing land.
- Size compatible with the lift capacity of most small loader tractors.
- Good forward visibility for easy control in close quarters for increased productivity.
- Simple efficient design with few moving parts for long life.
- Upper grapple is 34-inches wide for excellent material retention, controlled by single 2 x 8 cylinder.
- Pivot points have lubrication capabilities.
- Tractor front loader model allow use of standard pin-on bracket or select interfacing quick attach brackets for John Deere, AGCO, CNH, Kubota and other brands.
- Model FLGR-4062S is designed for compact tractor front loaders that are equipped with the “Universal” skid steer quick attach system. **It is not designed to be fit to a skid steer loader.**

## Designed for Tractors up to 40 HP Only

Overall width (in/mm) .....	60/ ( 1524 mm)
Overall depth (in/mm) .....	23/ ( 584.2 mm)
Overall height (closed) (in/mm) .....	38.77 / (984.75 mm)
Tine spacing (in/mm) .....	15 / (381 mm)
Grapple opening (in/mm) .....	27 / (685.8 mm)
Number of lower tines .....	5
Width of upper grapple (in/mm).....	34 / (836.6)
Reinforcing tubes between lower tines .....	Yes
Number of cylinders .....	1
Cylinder Specifications	
Bore (in/mm) .....	2 / (50.8 mm)
Stroke (in/mm) .....	8 / (203.2 mm)
Rod diameter (in/mm) .....	1.125 / (28.57 mm)
Pressure (psi/bar) .....	2500 / (172.4)

### Model FLGR-4062

Mounting Tractor Loader .....	Mgt Brt available *
Weight Skid Steer (lb./kg) .....	359 / (180.98 kg)
Product Computer Number Tractor Loader .....	811460

### Model FLGR-4062S

For Loaders with Skid Steer Mount .....	“Universal” Skid Steer+
Weight Skid Steer (lb./kg) .....	364/ (180.98 kg)
Product Computer Number Skid Steer .....	811480

*Be sure tractor is properly counterbalanced.*

\*Optional Quick Attach brackets available

**+ Not for use on skid steer loaders**



**READ AND UNDERSTAND OPERATOR'S MANUAL BEFORE OPERATION.**

Worksaver Inc. has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. Worksaver Inc. is not responsible for differences between specifications or illustrations contained in this publication and the actual equipment.

*Worksaver.*

*Designed.  
Engineered.  
Remarkable  
Value.*



**Worksaver, Inc.**

P.O. Box 100, Litchfield, IL 62056-0100  
Phone: 217-324-5973 • Fax: 217-324-3356  
E-mail: [sales@worksaver.com](mailto:sales@worksaver.com)  
Web: [www.worksaver.com](http://www.worksaver.com)

**Information Provided By:**



*Worksaver.*

*Designed.  
Engineered.  
Remarkable  
Value.*



## Grapple Rake Attachment

**Ideal for loading logs, picking up rocks, orchard prunings and piling brush and other hard to handle materials.**



# Worksaver®

## Grapple Rake for Skid Steer and Front Loader

- Ideal for loading logs, picking up rocks, orchard prunings, raking and piling brush and other hard to handle materials.
- Unique tine design with replaceable weld-on tine points.
- Tine points allow operator to go under logs and brush to completely pick them up.
- Design allows brush and other materials to be picked up while leaving the dirt.
- Great for picking up / piling cut trees and treetops when clearing land.
- Size compatible with the lift capacity of most machines.
- Good forward visibility for easy control in close quarters for increased productivity.
- Simple efficient design with few moving parts for long life.
- Skid Steer model use ‘Universal Attaching’ system to provide the operator with quick convenient method of installation.
- Tractor front loader model comes standard with pin type (1-inch) mounting channels. Optional quick attach mounting brackets are available for most popular quick attach bucket mountings.

### GRAPPLE RAKE SPECIFICATIONS

Overall width (in/mm) .....	62 / ( 1575 mm)
Overall depth (in/mm) .....	25 / ( 635 mm)
Overall height (closed) (in/mm) .....	54 / (1372 mm)
Tine spacing (in/mm) .....	15 / (381 mm)
Grapple opening (in/mm) .....	50 / (1270 mm)
Number of grapple tines .....	3
Number of cylinders .....	2
<b>Cylinder Specifications</b>	
Bore (in/mm) .....	2.5 / (63.5 mm)
Stroke (in/mm) .....	10 / (254 mm)
Rod diameter (in/mm) .....	1.125 / (28.57 mm)
Pressure (psi/bar) .....	2500 / (172.4)

#### Model FLGR-62

Mounting Tractor Loader .....	Std.Pin-type *
Weight Skid Steer (lb./kg) .....	660 / (300 kg)
Product Computer Number Tractor Loader .....	811120

#### Model SSGR-62

Mounting Skid Steer .....	“Universal” Skid Steer Weight
Skid Steer (lb./kg) .....	667 / (303 kg)
Product Computer Number Skid Steer .....	811130

*Be sure tractor / skid steer is properly counterbalanced.*

\*Optional Quick Attach brackets available



READ AND UNDERSTAND OPERATOR'S MANUAL BEFORE OPERATION.

Worksaver Inc. has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. Worksaver Inc. is not responsible for differences between specifications or illustrations contained in this publication and the actual equipment.

**Worksaver.**



**Worksaver, Inc.**

P.O. Box 100, Litchfield, IL 62056-0100  
 Phone: 217-324-5973 • Fax: 217-324-3356  
 E-mail: [sales@worksaver.com](mailto:sales@worksaver.com)  
 Web: [www.worksaver.com](http://www.worksaver.com)

Information Provided By:



*Worksaver.*

*Designed.  
Engineered.  
Remarkable  
Value.*



## Split-Top Grapple Rake Attachment

Designed for today's modern skid steer and tractor front loaders. Available in 62" or 77" width, the split top design provides dual upper grapples for picking up brush and other debris while leaving the dirt behind.



Worksaver.

Designed.  
Engineered.  
Remarkable  
Value.

## Worksaver® Grapple Rake for Skid Steer and Front Loader

- Ideal for loading logs, orchard prunings, raking and piling brush and other hard to handle materials.
- Unique tine design with replaceable weld-on tine points.
- Tine points allow operator to go under logs / brush for easy clean pick up.
- Interfacing quick-attach brackets available for most tractor loader models including John Deere, AGCO, CNH, Bush Hog and others.
- Greaseable pivot points on upper clamps for long service life.
- Shield Plate in upper clamps provides protection for hydraulic cylinders.

### SPLIT-TOP GRAPPLE RAKE SPECIFICATIONS

	FLGR-262 / SSGR-262	FLGR-277 / SSGR-277
Overall width (in/mm)	62 / 1575	77 / 1956
Overall depth (in/mm)	25 / 635	25 / 635
Overall height closed (in/mm)	54 / 1372	54 / 1372
Grapple opening (in/mm)	50 / 1270	50 / 1270
Upper grapple widths (in/mm)	19.25 / 489	19.25 / 489
Tine Spacing (in/mm)	15 / 381	15 / 381
Number of tines / grapples (lower / upper)	5 / 4	6 / 4
Reinforcing tubes between lower tines	Yes	Yes
Number of hydraulic cylinders	2	2
Cylinder bore (in/mm)	2 / 50.8	2 / 50.8
Cylinder stroke (in/mm)	10 / 254	10 / 254
Cylinder rod diameter (in/mm)	1.125 / 28.57	1.125 / 28.57
Cylinder pressure rating (psi/bar)	2500 / 172.4	2500 / 172.4
Mounting for Tractor Loader (FLGR)	Std. Pin Type *	Std. Pin Type *
Weight FLGR model (lb/kg)	790 / 358	970 / 440
Mounting for Skid Steer (SSGR)	"Universal" Skid Steer	"Universal" Skid Steer
Weight SSGR model (lb/mm)	786 / 784	966 / 964
Horse power rating (maximum)	95 PTO HP	150 PTO HP
Product No. FLGR models (loader)	811380	811400
Product No. SSGR models (skid steer)	811435	811440

*Be sure tractor / skid steer is properly counterbalanced.*

\*Optional Interfacing Quick Attach brackets available for most popular loaders.



**READ AND UNDERSTAND OPERATOR'S MANUAL BEFORE OPERATION.**

Worksaver Inc. has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. Worksaver Inc. is not responsible for differences between specifications or illustrations contained in this publication and the actual equipment.



**Worksaver, Inc.**

P.O. Box 100, Litchfield, IL 62056-0100  
Phone: 217-324-5973 • Fax: 217-324-3356  
E-mail: [sales@worksaver.com](mailto:sales@worksaver.com)  
Web: [www.worksaver.com](http://www.worksaver.com)

Information Provided By:

